

Chevaprime U

Areas Of Use:

A corrosion and stain resistant primer for use on galvanised steel, timber and timber composites, and interior board linings.

Product:

A waterborne modified acrylic primer, with special pigmentation to enhance stain-block and anti-rust capabilities.

Product Compatibility:

Use as a primer for:

Flexx	Acrutexx	Colourglaze
Coverall	Covercryn	Extracover
Dexx		

Standard Pack:

4, 10 and 20 litre plastic pails.

Physical Properties:

Liquid Material:

Solids (% by volume):	38%
Specific Gravity:	1.22
Flash Point:	Not applicable - waterborne material.
Shelf Life:	Three years in original sealed containers. Store in cool dry conditions and protect from frosts.

Applied Film:

Flexibility:	Passes 2mm mandrel
Adhesion:	Excellent adhesion to the surfaces listed in "Areas of Use", except on timbers such as Matai and Totara.
Fungus Resistance:	Chevaprime U contains a highly effective mould-resistant additive which does not contain toxic metals or phenols.

Surface Preparation:

Ensure surface to be coated is free of dust and contamination. Oil contamination on galvanised steel should be removed by scrubbing with clean water and detergent and rinsing well.

Timber and stopped board lining surfaces should be sanded and swept to remove all imperfections particularly where a smooth finish is required.

Application Method:

By brush, roller or spray direct from pail. Thinning is not normally required.

Application Properties:

Spreading rate:

Theoretical	10-12 sqm/litre
Practical	8-10 sqm/litre

Recommended film thickness:

35µm

Dry time:

Touch dry:	1-2 hours
Recoat time:	6-8 hours

Thinning/Cleanup:

Water

Health And Safety

Chevaprime U is a waterborne material, is non-flammable and contains no mammalian toxic substances. It requires no special storage conditions other than protection from frost. We recommend the use of barrier cream on exposed skin when handling this material.

Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214 Fax 03 578 0919
Email: admin@equus.co.nz
Web: www.equus.co.nz