



# Equus Gib Sealer

## Purpose & Areas Of Use:

A fast dry, early sandable sealer for use mainly on new Gibraltar Board surfaces.

## Product:

A 100% waterborne sealer acrylic pigmented with titanium dioxide and inert extenders.

## Process Compatibility:

Use as a primer/sealer under waterborne interior finishes.

## Colour:

Standard white. Specially tinted colours may be produced but will be subject to minimum quantities.

## Standard Pack:

4 litre, 15 litre plastic pails.

## Physical Properties:

### Liquid Material :

Solids (% by volume): 45%  
Specific Gravity: 1.66  
Flash Point: None - waterborne material.  
Shelf Life: 3 years in original sealed containers.  
Store in cool, dry conditions and protect from frost.

### Applied Film:

Adhesion: Excellent adhesion to Gibraltar Board and previously painted or sealed surfaces.  
Sanding Properties: Excellent within 2 hours of application. Sanding becomes more difficult as the surface progressively hardens to full cure.  
Film Thickness: 45 microns d.f.t. @ 10 sqm/litre

## Surface Preparation:

Ensure that the surface to be treated is flush and free of dirt and contamination. Stopped board lining surfaces shall be sanded and swept to remove all imperfections particularly when a smooth finish is required.

## Application Method:

By brush, roller, or spray direct from the container. Thinning is normally not required.

## Application Properties:

Spreading Rate: 10 sqm/litre  
Recommended Film Thickness: 45 microns  
Dry Time: Touch dry and sandable  
10 minutes on unsealed Gibraltar Board  
20 minutes on previously sealed or painted substrates.  
Thinning/Clean Up: Clean water.

## Application Conditions:

Do not apply at temperatures below 5°C or when temperatures are liable to fall below this while drying.

## Health And Safety:

**Equus Gib Sealer** is a waterborne material with low VOC, is non flammable and contains no mammalian toxic substances. It requires no special storage conditions other than protection from excessive heat and frost. We recommend the use of barrier cream on exposed skin when handling this material.

**Equus Industries Ltd**  
PO Box 601  
Blenheim  
Phone: 03 578 0214 Fax 03 578 0919  
Email: [admin@equus.co.nz](mailto:admin@equus.co.nz)  
Web: [www.equus.co.nz](http://www.equus.co.nz)