



513

1 page

PRODUCT
DATA
SHEET

Equus Graffitistrip

Purpose & Areas Of Use:

For the removal of surface applied graffiti from surfaces treated with the **Chevaline Clearcure Anti Graffiti System**.

Product:

A gel consisting of volatile and non-volatile solvents plus wetting agents for ease of application and removal.

Colour:

Clear gel.

Standard Pack:

1 litre, 4 litre metal screw top container.

Physical Properties:

% High Volatility Solvents	30%
% Medium Volatility Solvents	30%
% Low Volatility Solvents	30%
Specific Gravity	0.96
Flash Point	0°C

Handling And Storage:

Equus Graffitistrip is a volatile material and should be stored away from any heat source or naked flames.

Care should be taken not to splash **Equus Graffitistrip** on surrounding paint work or plants.

Method Of Use:

Equus Graffitistrip is applied by brush direct from the container. It should be applied to any graffiti to be removed as soon as the graffiti is discovered.

Apply sparingly and repeatedly test whether graffiti has softened sufficiently to be removed, by wiping a small area with a cloth. If so, wipe off excessive **Graffitistrip** with clean rags and then wash, and if necessary, lightly scrub the surface with a soft bristled brush and clean water.

If graffiti has not been completely removed, selectively repeat the process over these areas.

Note: Equus Graffitistrip, is an aggressive material which may, after long contact, affect the surface of the anti-graffiti coating. Therefore, it is important that contact time be kept to a minimum by not allowing the graffiti to harden on to the surface by delaying treatment, and by carefully checking when the graffiti has softened and remove it immediately this has occurred.

Health And Safety:

Equus Graffitistrip contains solvents and wetting agents and should be handled with care.

Wear gloves, eye protection and a solvent vapour mask when using. Protect exposed skin areas with an industrial barrier cream.

DO NOT SMOKE WHILE USING THIS MATERIAL.

After evaporation of the solvents from the product residues, the rags used to wipe the surface may be disposed of as industrial refuse.

Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214 Fax 03 578 0919
Email: admin@equus.co.nz
Web: www.equus.co.nz