



# Equus Lo Sheen

## Areas of Use:

An interior, low sheen/silk paint for use on most interior surfaces. Produces a smooth, tough, washable, burnish resistant finish.

## Product:

A 100% acrylic, water based finish pigmented with titanium dioxide and inert extenders. It is a low odour product formulated for application at temperatures as low as 3°C.

## Compatibility:

Use with Equus Gib Sealer, Chevaprime PBT and Chevaprime U depending upon surface to be coated.

May be applied as an interior topcoat to all Equus water-based texture finishes.

## Colour:

Available in most BS5252 and BS2660 colours. Special colour matching is available, but may be subject to minimum batch quantities. Some very bright or strong colours may incur a colour surcharge.

## Standard pack:

4, 10 and 20 litre plastic pails.

## Physical Properties:

Solids (% by volume): 37.2%  
Solids weight: 55.6%  
Specific gravity: 1.42  
Flash point: None - waterborne material  
Shelf life: 3 years in original sealed containers.  
Store in cool, dry conditions and protect from frost.

## Applied Film:

Adhesion: Excellent to recommended primers, sealers and most previously painted surfaces.

Abrasion resistance: Very good

Durability: Excellent

## Surface Preparation:

All surfaces to be coated must be cleaned to remove dirt, dust and any loose material. Ensure that the surfaces are also free of oil, grease or mould.

## Primers:

For Gib board: Equus Gib Sealer

For timber, fibrous plaster, hardboard, particle board, fibre-board: Chevaprime PBT

For advice on application to other surfaces, contact the nearest Equus Office.

## Application Properties:

By brush, speed brush, roller or conventional/airless spray.

Spreading rate: 10sqm/litre  
No. of coats: Normally 2 coats  
Dry film thickness/coat: 37 microns  
Dry time - Touch dry: 1 hour  
Recoat time: 2-4 hours  
(dry times at 21°C and 50% relative humidity)

## Application Conditions:

Do not apply at temperatures below 3°C or when temperatures are liable to fall below this while drying.

## Health & Safety:

Equus Lo Sheen is a waterborne material with Low VOC, is non flammable and contains no mammalian toxic substances.

It requires no special storage conditions other than protection from excessive heat and frost. We recommend the use of barrier cream on exposed skin when handling this material.

**Equus Industries Ltd**  
PO Box 601  
Blenheim  
Phone: 03 578 0214 Fax 03 578 0919  
Email: [admin@equus.co.nz](mailto:admin@equus.co.nz)  
Web: [www.equus.co.nz](http://www.equus.co.nz)