

Method Of Application:

Install Tremproof 60R by trowel and Tremproof 60H by squeegee, directly to the clean substrate. Apply at a minimum thickness of 1.5mm (1500 wet microns). This 1.5mm is in addition to the preparatory work. A slip sheet of heavy duty builders plastic must be installed between the membrane and any solid topping.

Health & Safety Precautions:

The Material Safety Data Sheet (MSDS) must be read and understood prior to use.

Storage:

Store in original unopened packaging in dry conditions between +5°C and +25°C.

Shelf Life:

12 months when stored as recommended in original unopened packaging.

Guarantee/Warranty:

Tremco products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco written instructions and (b) in any application recommended by Tremco, but which is proved to be defective, will be replaced free of charge.

Any information provided by Tremco in this document in relation to Tremco's goods or their use is given in good faith and is believed by Tremco to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. Tremco makes no representation, guarantee or warranty relating to the accuracy or reliability of the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214 Fax 03 578 0919
Email: admin@equus.co.nz