


NOTE: Fastener spacing to follow de Boer project specific engineered fixing plan.

Shrink Sleeve	
Internal diameter Body	Sleeve shrinkable to
18 mm	8 mm
22 mm	12 mm
42 mm	22 mm
55 mm	42 mm
66 mm	55 mm
88 mm	66 mm
110 mm	88 mm

- ① Concrete Roof Slab laid to Fall
- ② Equus/De Boer DuO Primer
- ③ Equus/De Boer Basesheet
- ④ Equus/De Boer Basesheet, over Plywood Plinth
- ⑤ Equus/De Boer Capsheet DuO HT 4 Slates/F C180 FireCare
- ⑥ Equus/De Boer Capsheet, as separate piece over Shrink Sleeve
- ⑦ Plywood Plinth
- ⑧ De Boer bitumen Flange attached to Shrink Sleeve Body
- ⑨ Equus/De Boer DuO Kit Sealant
- ⑩ Shrink Sleeve Body internal diameter 55 mm
- ⑪ Shrink Sleeve




equus
E-mail : admin@equus.co.nz
Web : www.equus.co.nz

**De Boer DuO Cold Roof on Concrete
Standard Pipe Penetration
with De Boer Shrink Sleeve**

Equus/De Boer Waterproof Membrane Details are specially drawn for use by Local Authorities, Building Contractors, Equus Applicators, Architects and design professionals. All details are drawn to assist in the development of project specific details. Details may be modified where necessary to accommodate job specific requirements but must be approved by Equus Industries Ltd. All components must be supplied by Equus Industries Ltd. Equus Industries Ltd. reserves the right to alter or upgrade details at any time without prior notice.

Drawing No:	DBCRC-D5
Scale:	1:3 @ A4
Drawn by:	NKT
Date:	11/10/2017



de boer
waterproofing solutions
E-mail : info@deboer.be
Web : www.deboer.be