



- ① Concrete Roof deck
- ② Equus/De Boer DuO Primer
- ③ Equus Vapour Barrier
- ④ Thermal Insulation Board
- ⑤ Equus 9mm PermaBase Dek Roof board
- ⑥ Equus De Boer DuO primer (50/50 diluted with white spirit) on Roof board
- ⑦ Equus/De Boer DeboFlex 2.5 T/F C175 base sheet
- ⑧ Equus/De Boer DuO HT 4 GW/F C180 FireCare Capsheet
- ⑨ Plywood Plinth
- ⑩ Equus/De Boer DuO Kit Sealant
- ⑪ Equus/De Boer Capsheet as separate piece over Plywood Plinth
- ⑫ Equus Matacyl liquid waterproofing
- ⑬ SHS penetration

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

⑬

⑪ ⑫

≥ 100 mm

≥ 150 mm

150 mm



E-mail : admin@equus.co.nz
Web : www.equus.co.nz

**DuOthem warm Roof on Concrete
Standard Pipe Penetration with Collar**

Equus/De Boer Waterproof Membrane Details are specially drawn for use by Local Authorities, Building Contractors, Equus Applicators, Architects and design professionals. All details are drawn to assist in the development of project specific details. Details may be modified where necessary to accommodate job specific requirements but must be approved by Equus Industries Ltd. All components must be supplied by Equus Industries Ltd. Equus Industries Ltd. reserves the right to alter or upgrade details at any time without prior notice.

Drawing No:	DBDTC-D5.2
Scale:	1:3 @ A4
Drawn by:	NKT
Date:	30-May-2019



E-mail : info@deboer.be
Web : www.deboer.be