



SAFETY DATA SHEET

SDS 177

PAGE 1 OF 8

1. Product and Company Identification

- 1.1 PRODUCT NAME:** CHEVALINE CLEARCURE
- 1.2 USE OF PRODUCT** High performance clear topcoat for walls to enhance wearing characteristics and provide graffiti protection, and for floors, in interior and exterior situations.
- 1.3 SUPPLIER:** Equus Industries Ltd
Sheffield Street
Riverlands Industrial Estate
Blenheim, Marlborough, New Zealand
Telephone: +64 3 578 0214
Fax: +64 3 578 0919
- 1.4 EMERGENCY CONTACT:** **National Poison Centre**
Telephone: 0800 764 766

Information about Safety Data Sheet: Telephone: +64 3 578 0214 8:00am – 6:00pm Mon – Fri

- 1.5 DATE OF PREPARATION:** 15 April 2013

2. Hazards Identification

- 2.1 Statement of Hazardous Nature:**
Classified as hazardous according to New Zealand Hazardous Substances (Minimum degrees of hazard) Regulations 2007.
- 2.2 HSNO Group Standard:**
Surface Coatings and Colourants (Flammable)
- 2.3 Substance Classification:**
3.1C, 6.1E, 6.3A, 6.4A, 6.5B, 6.8B, 6.9A, 9.1D
- 2.4 Hazard Statements:**
Flammable liquid and vapour.
May be harmful in contact with skin.
May be harmful if inhaled.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Suspected of damaging fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure.
May cause long lasting harmful effects to aquatic life.

**2.5 Prevention Statements:**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge..
Do not breathe fumes.
Wash thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection.
Use personal protective equipment as required.
In case of inadequate ventilation wear respiratory protection.

3. Composition/Information on Ingredients

CAS NO.	COMPONENT	CONCENTRATION (% Weight)
-	Aliphatic polyisocyanate Prepolymer	30-60
108-65-6	1-Methoxy-2-propanol acetate	10-30
64742-95-6	Solvent Naphtha 100	10-30
1330-20-7	Xylene	<10.0
122-51-0	Triethyl orthoformate	<1.0

4. First Aid Measures**4.1 After Inhalation:**

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If required, artificial respiration or administration of oxygen can be performed by trained personnel. If symptoms persist, seek medical attention.

4.2 After Skin Contact:

Remove/take off all contaminated clothing. Wash area of contact thoroughly with plenty of soap and water. If irritation, rash or other disorders develop, seek medical attention immediately. Wash contaminated clothing before re-use.

4.3 After Eye Contact:

Rinse cautiously with water for at least 15 minutes while holding eye lids apart. Remove contact lenses if present and easy to do. Continue rinsing. If irritation persists, seek medical advice/attention.

4.4 After Ingestion:

Immediately call Poison Centre or Doctor/Physician.

4.5 General:

Get immediate medical attention for any significant over exposure..

4.6 Advice to Doctor:

Treat symptomatically.

**5. Fire Fighting Measures****5.1 Suitable Extinguishing Media:**

If water fog is ineffective, use carbon dioxide, dry chemical or foam.

5.2 Protective Equipment:

Use accepted firefighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water may be used to cool containers to minimise pressure build-up.

5.3 Specific Hazards:

Product may ignite if heated in excess of its flashpoint. Closed container may burst when exposed to extreme heat. Empty containers may contain ignitable vapours. Vapours may travel to sources of ignition and flash back.

5.4 Combustion Products:

Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.

5.5 Fire and Explosion Conditions:

Product may ignite if heated in excess of its flashpoint.
Vapours may travel to source of ignition and flashback.
Closed container may burst when exposed to extreme heat.
Containers may contain ignitable vapours.

5.6 Additional Information:

Flashpoint = 32°C (Closed Cup, Hazchem Code 3[Y]).

6. Accidental Release Measures**6.1 Preliminary Action and Precautions:**

6.1.1 Eliminate very possible source of ignition.

6.1.2 Evacuate all personnel immediately and ventilate area.

6.1.3 Avoid breathing vapour and contact with skin, eyes and clothing.

6.1.4 Wear recommended personal protective equipment.

6.1.5 Shut off leaks if possible without risk.

6.1.6 Dike in the spilled product as much as possible with inert material..

6.1.7 Prevent entry of product into sewers, storm water drains and open bodies of water.

6.1.8 Clean up all spills as soon as possible, using an inert absorbed material and dispose of as hazardous waste.

**7. Handling and Storage****7.1 Handling:**

- 7.1.1 Prevent inhalation of vapour, ingestion and contact with skin, eyes and clothing.
- 7.1.2 Keep container closed when not in use. Precautions also apply to emptied containers.
- 7.1.3 Change soiled work clothing frequently.
- 7.1.4 Clean hands thoroughly after handling.
- 7.1.5 Do not smoke, weld, generate sparks, or use flame near container.
- 7.1.6 To prevent generation of static discharges, use bonding/grounding connection when pouring liquid.
- 7.1.7 Extinguish all ignition sources including pilot lights, and do not use non-explosion proof motors and electrical equipment until vapours dissipate.

7.2 Storage:

- 7.2.1 Store under dry warehouse conditions.
- 7.2.2 Store away from sources of ignition, (i.e. sparks, open flames, heat etc)
- 7.2.3 Store away from strong acids, strong bases, amines, water or moisture, and alcohols.
- 7.2.4 Keep containers tightly closed at all times.

8. Exposure Controls and Personal Protection Equipment**8.1 Exposure Limits:**

CHEMICAL NAME	CAS NUMBER	REGULATION	LIMIT
Xylene	1330-20-7	WES – TWA	50ppm 217mg/m ³
1 Methoxy-2-propanol acetate	108-65-6	ACGIG – TWA ACGIH – STEL	20ppm 50ppm
Solvent Naphtha 200	64742-96-6	ACGIH – TWA ACGIH - STEL	20ppm 100mg/m ³ 50ppm 250mg/m
Aliphatic Polyisocyanate Prepolymer	-	WES - TWA WES – STEL	0.02mg/m ³ 0.07mg/m ³

8.2 Exposure Controls:**8.2.1 Exposure Controls in the Work Place:**

Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.



8.2.2 Personal Protection Equipment

Respiratory Protection – Wear appropriate, properly fitted NIOSH/MSHA, approved respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the SDS. Select positive pressure supplied air respirator for isocyanates, (TC 19c or equivalent).

Hand Protection – Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.

Eye Protection – Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.

Skin/Body Protection - Prevent contact with shoes and clothing.

Protective Measures - Use professional judgment in the selection, care, and use.

9. Physical and Chemical Properties

9.1 General Information:

Physical State/Form	Liquid
Colour	Clear
Odour	Hydrocarbon/acetate solvent
pH	Not applicable
Flash Point	32°C (closed cup)
Water Solubility/Miscibility	Negligible.
Specific Gravity	1.04
% Volatile Weight	43%
VOC (less water and exempt Solvent)	465g/l

10. Stability and Reaction

10.1 General Information:

This material is stable when properly handled and stored.

10.2 Conditions to Avoid:

High temperatures, open flames, sparks..

10.3 Material to Avoid:

Strong acids, strong bases, amines, water or moisture and alcohols.

10.4 Hazardous Decomposition Products:

None expected when material properly handled and stored. For thermal decomposition see Section 5.

10.5 Hazardous Polymerisation:

Will not occur under normal conditions.

**11. Toxicological Information****11.1 Health Effects/Symptoms of Exposure:**

Vapour and/or mist may irritate nose and throat. Leave area to breathe fresh air. Avoid further over exposure. If symptoms persist, seek medical attention.

11.2 Acute toxicity:

1-Methoxy-2 propanol acetate. CAS No. 108-65-6

Oral LD50 (Rat) 8,532 mg/kg

Dermal LC50 (Rabbit) >5,000 mg/kg

Solvent Naphtha 100 CAS No. 64742-95-6

Oral LD50 (Rat) 6,800 mg/kg

Dermal LC50 (Rabbit) 3,400 mg/kg

Inhalation LD50 (Rat) 1,970 ppm/4 hours

Xylene CAS No. 1330-20-7

Oral LD50 (Mouse) 1,590 mg/kg

Inhalation LC50 (Rat) 27.6 mg/kg

11.3 Skin Contact:

May cause sensitization resulting in irritation, itching and redness.

11.4 Eye Contact:

Vapours and/or mist may cause eye irritation.

11.5 Ingestion:

May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea and vomiting.

11.6 Inhalation:

May cause drowsiness, weakness, and fatigue. Vapour and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization.

11.7 Chronic Effects:

Unless suitable engineering controls and/or personal protective equipment is used:

- Repeated over-exposure to vapour may lead to asthma and sensitization or damage to the respiratory system.
- Repeated unprotected physical contact with the material may cause defatting of the skin leaving it vulnerable to irritation, dermatitis and/or sensitization.
- Prolonged over exposure to vapour and/or unprotected physical contact may lead to internal organ sensitization and/or damage. The Central Nervous System may also be affected.

12. Ecological Information**12.1 Environment Protection:**

Prevent from entering drains, sewers and waterways.



- 12.2 Ecotoxicity:**
May cause long lasting harmful effects to aquatic life.
- 12.3 Persistence and degradability:**
Data not available.
- 12.4 Bioaccumulative Potential:**
Data not available.

13. Disposal Consideration

13.1 Disposal Methods

Subject to hazardous waste treatment, storage and disposal requirements. Recycle or incinerate waste at approved facility or dispose of in compliance with national/regional/local, waste disposal regulations. DO NOT EMPTY INTO DRAINS, SEWERS OR WATERWAYS.

14. Transport Information

- 14.1** Regulated under NZS 5433 for land transport.

UN Number	1263
Proper Shipping Name	Paint Related
Class	3
Packing Group	III
Hazchem Code	3[Y]

15. Regulatory Information

- 15.1 HSNO Approval:**
- | | |
|---------------------|---|
| Approval Code | HSR 002662 |
| HSNO Group Standard | Surface Coatings and Colourants (Flammable) |
- 15.2 HSNO Controls:**
- | | |
|------------------|--------------|
| Approved Handler | Not required |
|------------------|--------------|

16. Other Information

16.1 Hazard/Classifications:

3.1C	Flammable Liquid – medium hazard.
6.1E	Substances that are acutely toxic. May be harmful. Aspiration hazard.
6.3A	Substances that are irritating to the skin.
6.4A	Substances that are irritating to the eye.
6.5A	Substances that are respiratory sensitizers.
6.5B	Substances that are contact sensitizers.
6.8B	Substances that are suspected human reproductive or developmental toxicants.



- 6.9A Substances that are toxic to human target organs or systems.
9.1D Substances that are slightly harmful to the aquatic environment or are otherwise designed for biocidal action.

16.2 Abbreviations/Terminology:

HSNO	Hazardous substances and New Organisms Act
CAS	Chemical Abstract Service
ACGIH	American Conference of Governmental Industrial Hygienists
LD50, LC50	Lethal dose/Lethal Concentration – Dose or concentration required to produce the specified effect in 50% of the sample studied.
WES	Workplace Exposure Standard (NZ Department of Business, Innovation and Employment)
TWA	Time weighted average exposure level designed to protect from the effects of long-term exposure.
STEL	Short-term Exposure Level (15 minutes)
VOC	Volatile Organic Compound

16.3 Issue Information:

Date of Preparation:	15 April 2013
Reasons:	Update and format change
Replaces:	1 July 2007

- 16.4 The information contained in this Data Sheet relates only to the specific material identified. Equus Industries Ltd believes the information to be accurate and reliable as at the date of this Data Sheet. No Warranty, Guarantee or representation is expressed or implied by the Company as to the absolute correctness or completeness of any representation contained in this Data and assumes no legal responsibility in connection therewith. It can not be assumed that all acceptable safety measures are contained in this Data Sheet, or that additional measures may not be required under particular or exceptional circumstances or conditions.