

CHEVALINE COVERALL PRIMER SEALER

Primer/sealer for all cement base surfaces

April 2024

PURPOSE AND AREAS OF USE:

A ready for use primer/sealer for all cement base surfaces.

PRODUCT:

A waterborne acrylic primer with excellent adhesion properties. Compatible for use with all Chevaline water base coating and membrane systems.

COLOUR:

Off-white.

STANDARD PACKS:

5 and 15 litre plastic pails.

PHYSICAL PROPERTIES:

Liquid Material	
Solids (% by volume)	42%
Specific Gravity	1.2
Flash Point	None - Waterborne material.
Shelf Life	3 years in original sealed containers, when stored in cool dry conditions.

Applied Film	
Flexibility	Passes 2 mm mandrel
Durability	Excellent. Possesses indefinite life and retains flexibility when correctly topcoated and maintained.
Fungus Resistance	Coverall Primer Sealer contains a highly effective mould resistant additive which does not contain toxic metals or phenols.

SURFACE PREPARATION:

If moss or mould is present, moss killing must be carried out as a first step. Water-blasting is the most effective preparation on cementitious surfaces prior to primer application. It must be ensured that the surface is dry, free of loose material, dirt, dust, oil, grease, and mould prior to application. Efflorescence on concrete and cement plaster must also be removed.

APPLICATION METHOD:

Use brush or roller.

Spray application is not recommended for a primer coat.

APPLICATION PROPERTIES:

Spreading Rate:

On cement plaster and concrete	Use directly from the pail, apply at 8 sqm/litre.
On fibre reinforced cement boards	Dilute 3 volumes of Coverall Primer Sealer with 1 volume of clean water. Apply at 10 sqm/litre.

Dry times (at 20°C):

Touch dry	1-2 hours
Recoat time	4-6 hours

Thinning/Cleanup: Use clear water for both.

CHEVALINE COVERALL PRIMER SEALER

Primer/sealer for all cement base surfaces

April 2024

HEALTH AND SAFETY:

Chevaline Coverall Primer Sealer is a waterborne material, is non flammable and contains no mammalian-toxic substances. It requires no special storage conditions other than protection from frost. The use of barrier cream on exposed skin when handling this product is recommended.

WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No
--	----

MANUFACTURERS CONTACT DETAILS:

Manufacture location	New Zealand
Legal and trading name of manufacturer	Equus Industries Ltd.
Manufacturer address for service	4 Sheffield Street, Blenheim 7274
Manufacturer website	www.equus.nz
Manufacturer email	info@equus.nz
Manufacturer phone number	03 578 0214
Manufacturer NZBN	9429032000306