

Vulkem Primer 191

Key Benefits Summary:

- Fast Drying
- Adhesion Promoter

Product Description:

Vulkem Primer #191 is a one-part amber coloured liquid and is used to enhance the adhesion of Vulkem urethanes to many other generic coatings.

Basic Uses:

Primer #191 is a film forming adhesion promoter used to enhance adhesion of Vulkem urethane to Vulkem urethane sealants, Vulkem urethane membranes and Vulkem urethane deck coatings when required. Primer #191 may be used with Vulkem one-part or two-part materials.

Primer #191 may adhere to other new or aged generic coatings. A test patch should be applied to determine cleaning and surface preparation procedures; and to evaluate inter-coat adhesion between the old and freshly applied coatings. For primer recommendations, consultation with the local Equus representative is advised.

Limitations:

Must be applied at the correct application rate, with no ponding. Use with adequate ventilation. Not to be applied over tar or asphalt B.U.R.

Colour:

Amber

Packaging:

Available in 3.785L cans and 19L pails.

Usage Guidelines:

Application:

Vulkem Primer #191 must be applied to dry, dust and grease free surfaces. Apply primer with brush or roller. Do not spray. Allow to dry until tacky (about 30 minutes). Sealants, membranes or coatings must be applied before the #191 Primer is cured hard.

Coverage:

10.1-12.7m²

Technical Information:

Test	Results
Solids (weight)	12% (+/- 1%)
Weight	895g per litre
Viscosity (25°C)	124-32 CPS
Colour	Amber
Flash Point	26°C

Health and Safety Precautions:

Material Safety Data Sheet must be read and understood before use.

Guarantee/Warranty:

We warrant our products to be free of defects and manufactured to meet published physical properties when tested according to applicable specifications and TREMCO standards. Under this warranty we will provide at no charge, product to replace any product proven to be defective when applied in accordance with our written instructions and in applications recommended by TREMCO as being suitable for this product. All claims concerning product defects must be made within 12 months of shipment. Absence of such claims in writing during this period will contribute a waiver of all claims with respect to such product. This warranty is in lieu of any and all other warranties expressed or implied.

Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214
Email: admin@equus.nz
Web: www.equus.nz