

EQUUS MOSSKILL

For killing/neutralisation of most mosses, moulds and algae

July 2024

PURPOSE AND AREAS OF USE:

For killing/neutralisation of most mosses, moulds and algae growth on common building surfaces. Can also be used as a penetrating inhibitive treatment before overcoating with waterborne Equus coatings.

COLOURS:

As supplied - clear brown solution.
When diluted - white emulsion.

STANDARD PACKS:

1, 4 and 20 litre plastic containers.

PHYSICAL PROPERTIES:

Property	Value
Specific gravity	1.01
Flash point	>50°C

METHOD OF USE - CURATIVE:

Equus Mosskill is applied by brush, broom or spray after dilution. The solution ready for use is prepared by adding 500ml (0.5 litres) Equus Mosskill to 20 litres of water. Dilution is immediate, and the material is ready for use.

Spreading rates are determined by the degree of infestation, but generally the surface to be treated should be saturated with Mosskill solution, which should be allowed to react for 12-24 hours before removing all treated contamination by scraping and/or water-blast cleaning.

Heavy growths may require two applications.

A normal material usage would be 20-40 litres of prepared solution per 100 sqm of surface area.

METHOD OF USE - INHIBITIVE:

On clean surfaces, Equus Mosskill solution, prepared at a 1:40 dilution ratio, may be applied by spray or brush at a usage rate of 10-20 litres per 100 sqm of surface.

Overcoating may be carried out as soon as the surface has dried.

HANDLING AND STORAGE:

When using Equus Mosskill, make every effort not to apply the material to adjacent ornamental plants and vegetables. The solution may damage some plant species.

Always store in cool dry conditions. Only make up diluted solution that is likely to be used within 24-36 hours. Diluted material will lose its effectiveness on prolonged storage.

HEALTH AND SAFETY:

Equus Mosskill is prepared biocide and should be handled with care. The undiluted material is mildly irritating to the skin and corrosive to the eyes. Always wear protective rubber/plastic gloves and goggles when handling the material, in either concentrated or diluted form. Wear a chemical vapour mask when applying by spray.

Equus Mosskill is biodegradable and it is safe to dispose of residues in industrial sewage systems.



801

2 Pages

TECHNICAL
DATA
SHEET

Page 2 of 2

EQUUS MOSSKILL

For killing/neutralisation of most mosses, moulds and algae

July 2024**WARNINGS AND BANS:**

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No
--	----

MANUFACTURERS CONTACT DETAILS:

Manufacture location	New Zealand
Legal and trading name of manufacturer	Equus Industries Ltd.
Manufacturer address for service	4 Sheffield Street, Blenheim 7274
Manufacturer website	www.equus.nz
Manufacturer email	info@equus.nz
Manufacturer phone number	03 578 0214
Manufacturer NZBN	9429032000306