

821 2 Pages

TECHNICAL DATA SHEET

Page 1 of 2

CHEVALINE CLEARSTRIP

Deep penetrating stripper for paint, varnish and polish films

July 2024

PURPOSE AND AREAS OF USE:

As a safe, gentle-acting but deep penetrating stripper for paint, varnish and polish films on non or semi-porous surfaces. Formulated for easy removal by scrubbing or water jetting.

PRODUCT:

A waterborne mildly alkaline clear stripper with mild odour. Contains detergent aids for easy cleaning.

PRODUCT COMPATIBILITY:

This product will remove most waterbourne coatings, conventional enamels and varnishes, acrylic glazecoats and floor polish systems.

Clearstrip is recommended for use as the cleaner for sacrificial Clearglaze anti-graffiti systems and Clearseal hard-use areas.

Not recommended for the removal of epoxy, polyurethane and chlorinated rubber coatings. Check for suitability on any surface to be stripped before proceeding with large areas.

COLOUR:

Water-white

STANDARD PACKS:

4 and 20 litre plastic pails.

PHYSICAL PROPERTIES:

Property	Value
Specific gravity	1.22
Flash point	Not applicable - waterborne material

APPLICATION PROPERTIES:

Remove all easily removed dirt by sweeping or brushing, and apply Clearstrip by brush or roller as a heavy even layer to the surface to be cleaned.

Spreading rate will be 2-4 m²/litre depending on build-up of coating layer to be removed, and surface profile.

Leave Clearstrip on the surface for 30-60 minutes, checking periodically to determine softening of the coating layer and depth of penetration. The "peeling" effect occurs quite suddenly after a period of 30+ minutes, even though little seems to have occurred up to that time.

When "peeling" is evident back to original surface, remove the softened amalgam of Clearstrip coating by vigorous brushing with a stiff bristle brush, or preferably by water jetting.

Check cleaned surface for any residual patches and reapply Clearstrip where necessary.

Finally, hose down the stripped surface and allow to dry before any coating re-application is carried out.

HEALTH AND SAFETY:

Chevaline Clearstrip contains both alkaline and solvent base materials. Wear gloves and goggles when handling Clearstrip to prevent skin defatting, and eye-splash respectively. Wear PVC or rubber gumboots when working on floor surfaces. Always relid pails when not in use, and keep away from foodstuffs.



821

2 Pages

TECHNICAL DATA SHEET

Page 2 of 2

CHEVALINE CLEARSTRIP

Deep penetrating stripper for paint, varnish and polish films

July 2024

WARNINGS AND BANS:

|--|

MANUFACTURERS CONTACT DETAILS:

Manufacture location	New Zealand
Legal and trading name of manufacturer	Equus Industries Ltd.
Manufacturer address for service	4 Sheffield Street, Blenheim 7274
Manufacturer website	www.equus.nz
Manufacturer email	info@equus.nz
Manufacturer phone number	03 578 0214
Manufacturer NZBN	9429032000306