

823

2 Pages

TECHNICAL DATA SHEET

Page 1 of 2

EQUUS GRAFFITISTRIP

July 2024

PURPOSE AND AREAS OF USE:

For the removal of surface applied graffiti from surfaces treated with the Chevaline Clearcure Anti Graffiti System.

PRODUCT:

A gel consisting of volatile and non-volatile solvents plus wetting agents for ease of application and removal.

COLOUR:

Clear gel.

STANDARD PACKS:

1 litre, 4 litre metal screw top container.

PHYSICAL PROPERTIES:

Property	Value
% High volatility solvents	30%
% Medium volatility solvents	30%
% Low volatility solvents	30%
Specific gravity	0.96
Flash point	0°C

METHOD OF USE:

Equus Graffitistrip is applied by brush direct from the container. It should be applied to any graffiti to be removed as soon as the graffiti is discovered.

Apply sparingly and repeatedly test whether graffiti has softened sufficiently to be removed, by wiping a small area with a cloth. If so, wipe off excessive Graffitistrip with clean rags and then wash, and if necessary, lightly scrub the surface with a soft bristled brush and clean water.

If graffiti has not been completely removed, selectively repeat the process over these areas.

Note: Equus Graffitistrip is an aggressive material which may, after long contact, affect the surface of the anti-graffiti coating. Therefore, it is important that contact time be kept to a minimum by not allowing the graffiti to harden on to the surface by delaying treatment, and by carefully checking when the graffiti has softened and remove it immediately this has occurred.

HANDLING AND STORAGE:

Equus Graffitistrip is a volatile material and should be stored away from any heat source or naked flames.

Care should be taken not to splash Equus Graffitistrip on surrounding pain work or plants.

HEALTH AND SAFETY:

Equus Graffitistrip contains solvents and wetting agents and should be handled with care.

Wear gloves, eye protection and a solvent vapour mask when using. Protect exposed skin areas with an industrial barrier cream.

DO NOT SMOKE WHILE USING THIS MATERIAL.

After evaporation of the solvents from the product residues, the rags used to wipe the surface may be disposed of as industrial refuse.



823

2 Pages

TECHNICAL DATA SHEET

Page 2 of 2

EQUUS GRAFFITISTRIP

July 2024

WARNINGS AND BANS:

the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No
---	----

MANUFACTURERS CONTACT DETAILS:

Manufacture location	New Zealand
Legal and trading name of manufacturer	Equus Industries Ltd.
Manufacturer address for service	4 Sheffield Street, Blenheim 7274
Manufacturer website	www.equus.nz
Manufacturer email	info@equus.nz
Manufacturer phone number	03 578 0214
Manufacturer NZBN	9429032000306